

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-123325

(43)Date of publication of application : 28.04.2000

(51)Int.Cl.

G11B 5/39

(21)Application number : 11-290197

(71)Applicant : READ RITE CORP

(22)Date of filing : 12.10.1999

(72)Inventor : LIEN CHANG WANG  
CHI-FANG RAI  
TAI MIN  
ZUPEI SHI  
BILLY W KLUGH JR

(30)Priority

Priority number : 98 173472 Priority date : 14.10.1998 Priority country : US


## (54) METHOD AND DEVICE FOR PROVIDING SPIN-DEPENDENT TUNNELLING EFFECT INTO READING HEAD

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a reading sensor with which formation of short-circuit path between plural electrically conductive layers of a reading sensor is prevented and interlayer boundary surface control of high grade is realized and a manufacturing method thereof.

SOLUTION: A SDT(spin-dependent tunnelling effect) reading sensor has a first ferromagnetic material(FM) layer and a second FM layer separated by an insulating layer. The first FM layer and the second FMN layer are substantially electrically separated from each other. A sidewall of the SDT reading sensor substantially does not contain a conductive path between the first FM layer and the second FM layer. Further, a surface of the second FM layer extending substantially parallel to an air-bearing surface retreats from the air-bearing surface. A manufacturing method of the SDT reading sensor contains a process for depositing the first FM material layer, a process for depositing an intermediate insulating material layer on the first FM material layer and a process for depositing the second FM material layer on the intermediate insulating material layer.

The second FM material layer and the intermediate insulating material layer are subjected to etching. The etching is stopped before the first FM material layer is etched.



BEST AVAILABLE COPY

### LEGAL STATUS

[Date of request for examination]